

HOFFMAN HIGH SECURITY DISPLAY

Set up and Care Instructions

1. Locks

Display cases come without lock cores. Lock cores can be acquired through a locksmith or directly from a manufacturer like Delta Lock. www.deltalock.biz or (855) 803-3582. The lock core is XI CORE 7EBC UNCO. A control key is also required to install the lock core and should be purchased with the standard key. The lock core must be installed with the lock in the locked position so the key retain feature works. Use the plastic green actuator key (included with your display case) to position.



2. Electrical

Electrical specifications per display case: 120v with 20amp duty connection with LED 24v drawing 700mA per display case. All display cases have identical electrical assembly with LED power supply and are UL (Underwriter Laboratories) Listed.

Each display case connects to adjacent display case via metal locking plugs. Metal locking plugs are male/female. Establish which end of run where power drop is before connecting display case. Male/female can connect in either direction. Any metallically shielded wire should be secured in toe kick of display case. Starter assembly box should be secured and hardwired at power drop

3. Glass Shelves

For shipping, the glass shelves are on the floor of the display area. After the display case is in position, the shelves can be placed. The edges of the shelves will scratch the polycarbonate sides if this is not done carefully. There is a 10" and 14" shelf with the 10" on top; the 14" shelf beneath. Install one 10" shelf bracket on either the left or right side. Lift one end of the 10" shelf and place on bracket. Lift other side of shelf up and install bracket at other end. Install center bracket and rest shelves on brackets. Do the same for the 14" shelf.



4. Cleaning

Polycarbonate can scratch. While we have a protective tempered $\frac{1}{4}$ " glass on top and abrasion resistant laminate on the outside of the other polycarbonate panels, care should be taken in cleaning.

The Number 1 Problem with caring for polycarbonate sheet is the use of incorrect cleaners.

Please... never, ever, use cleaners containing ammonia. Cleaners such as Windex or 409 will harm polycarbonate. Use only products specifically recommended for cleaning polycarbonate such as Novus #1, or Brillianize, and a soft cloth. Never use a dry cloth or your hand to clean polycarbonate! This rubs the dirt and dust INTO the polycarbonate as much as it rubs it off.

To properly clean, first, blow the dust or dirt off, or use water and a soft cloth to float the dirt off. Then use a recommended cleaner to complete the job. Note: a mild solution of dish detergent and warm water takes off stubborn dirt easily without harming the polycarbonate if you've run out of Novus #1 or Brillianize. When in doubt, use water and a soft cloth.